

<b>GOLF ROTOR STATOR CONFIGURATION</b>					
	PRESSURE SETTINGS PSI (BARS)				ALL SAM/HYD
NOZZLE	60 (4,1)	70 (4,8)	80 (5,5)	100 (6,9)	AND BLOCK
500/550			·		
Beige #52	S4	S4	S4	S4	S4
Gray #53	S4	S4	S4	S4	S4
Red #54	S8	S8	S8	S8	S8
700					
White #28	SPC	SPC	SPC	SPC	SPC
Blue #32	SPO	SPO	SPO	SPO	SPO
Yellow #36	SPO	SPO	SPO	SPO	SPO
Orange #40	SNP	SNP	SNP	SNP	SNP
Green #44	SNP	SNP	SNP	SNP	SNP
Black#48	N/R	SNP	SPR	SPR	SNP
751			· · · · · ·		
White #28	SPC	SPC	SPC	SPC	SPC
Blue #32	SPO	SPO	SPO	SPO	SPO
Yellow #36	SPO	SPO	SPO	SPO	SPO
Orange #40	SNP	SNP	SNP	SNP	SNP
Green #44	SNP	SNP	SNP	SNP	SNP
Black#48	SNP	SPR	SPR	SPR	.SNP
900		•	· · · ·		
Blue #44	SPC	SPC	SPC	SPC	SPC
Yellow #48	SPC	SPC	SPC	SPC	SPC
Orange #52	SPC	SPO	SPO	SPO	SPO
Green #56	N/R	SNP	SNP	SNP	SNP
Black#60	N/R	SNP	SPR	SPR	SPR
Brown #64	N/R	SPR	SPR	SPR	SPR
950					
White #18C	SPC	SPC	SPC	SPC	SPC
Gray #20C	SPC	SPC	SPC	SPC	SPC
Blue #22C	SPC	SPC	SPC	SPC	SPC
Yellow #24C	SPC	SPC	SPO	SPO	SPO
Orange #26	SPO	SPO	SPO	SPO	SPO
Green #28	N/R	SNP	SPR	SPR	SPR
Black#30	N/R	SNP	SPR	SPR	SPR
Brown #32	N/R	SNP	SPR	SPR	SPR

500/551 - S 4 Hole Stator is Black S 8 Hole Stator is White

Stators normally black on 900/950 series (as below)



Stators normally white on 700/751 (as below)



Spacers are normally white with more open fins (as below)

700/751





SPC = Stator Poppet Closed

SPO = Stator Poppet Open

 $\mathsf{SNP} = \mathsf{Stator} \ \mathsf{No} \ \mathsf{Poppet}$ 

SPR = Spacer

S0 = Screen Only

 $\mathsf{S4}\ =\mathsf{Stator}\ \mathsf{with}\ \mathsf{4}\ \mathsf{holes}$ 

 $\mathsf{S8}\ =\mathsf{Stator}\ \mathsf{with}\ \mathsf{8}\ \mathsf{holes}$ 

 $N/R\,{=}\,Not$  a recommended pressure and nozzle combination