

MP ROTATOR® 800

Radius: 1.8 to 4.9 m

20
mm/hr

The MP800 offers a higher precipitation rate perfect for small spaces and spray retrofits.

KEY BENEFITS

- Precipitation rate of approximately 20 mm/hr for spray retrofit applications
- Automatic matched precipitation for simplified irrigation design and flexibility
- Double-pop feature protects the nozzle from external debris
- High distribution uniformity for a healthy landscape with maximum water efficiency

ADDITIONAL FEATURES

- Wind-resistant, multi-stream technology prevents misting
- For vandal resistance, the arc is adjustable only when the MP Rotator is running
- Removable filter screen prevents nozzle clogging
- Colour-coded for easy identification

OPERATING SPECIFICATIONS

- Radius reduction up to approximately 25% on all models
- Recommended operating pressure: 2.8 bar; 280 kPa
- Minimum radius setting achieved at 2.1 bar; 210 kPa
- Filtration recommended on dirty water applications
- Warranty period: 3 years

OPTIONS

- Pair with Pro-Spray™ PRS40 Sprinkler Body for pressure regulation to 2.8 bar; 280 kPa for nominal radius settings
- Pair with Pro-Spray PRS30 Sprinkler Body for pressure regulation to 2.1 bar; 210 kPa for minimum radius settings

MP800SR: 1.8 m to 3.5 m radius



MP800SR-90
90° to 210°



MP800SR-360
360°

MP815: 2.5 m to 4.9 m radius



MP815-90
90° to 210°



MP815-210
210° to 270°



MP815-360
360°

Compatible with:



HY Filter



PRS30 and PRS40

MP800SR-90



MP815-90



MP ROTATOR PERFORMANCE DATA

MP800SR

Radius: 1.8 to 3.5 m

Adjustable Arc and Full-Circle

● Orange and Grey: 90° to 210°

● Lime Green and Grey: 360°

MAX RADIUS							MIN RADIUS			
Arc	Pressure		Radius	Flow		Precip. mm/hr	Radius	Flow		
	bar	kPa	m	m ³ /hr	l/min	■ ▲	m	m ³ /hr	l/min	
90° 	2.1	200	2.6	0.04	0.61	22 25	1.8	0.03	0.49	
	2.5	250	2.9	0.04	0.72	21 24	2.1	0.03	0.55	
	2.8	280	3.1	0.05	0.87	21 24	2.4	0.04	0.61	
	3.0	300	3.4	0.06	0.95	20 23	2.4	0.04	0.68	
	3.5	350	3.5	0.06	1.02	20 23	2.7	0.04	0.72	
	3.8	380	3.5	0.06	1.06	20 23	3.0	0.05	0.76	
180° 	2.1	200	2.6	0.07	1.21	22 25	1.8	0.06	0.98	
	2.5	250	2.8	0.08	1.40	21 24	2.1	0.07	1.10	
	2.8	280	3.0	0.10	1.59	21 24	2.4	0.07	1.21	
	3.0	300	3.3	0.10	1.74	19 22	2.4	0.08	1.36	
	3.5	350	3.4	0.11	1.82	19 22	2.7	0.09	1.44	
	3.8	380	3.5	0.11	1.89	18 21	3.0	0.09	1.51	
210° 	2.1	200	2.6	0.08	1.40	22 25	1.8	0.07	1.15	
	2.5	250	2.8	0.10	1.67	22 25	2.1	0.08	1.28	
	2.8	280	3.0	0.11	1.85	21 24	2.4	0.08	1.41	
	3.0	300	3.2	0.12	2.01	20 23	2.4	0.10	1.59	
	3.5	350	3.4	0.13	2.12	19 22	2.7	0.10	1.68	
	3.8	380	3.5	0.13	2.20	18 21	3.0	0.11	1.77	
360° 	2.1	200	2.6	0.14	2.38	22 25	1.8	0.11	1.78	
	2.5	250	2.8	0.16	2.65	20 23	2.1	0.12	1.97	
	2.8	280	3.0	0.18	2.95	20 23	2.4	0.13	2.12	
	3.0	300	3.1	0.19	3.22	20 23	2.4	0.13	2.23	
	3.5	350	3.3	0.20	3.33	19 21	2.7	0.14	2.38	
	3.8	380	3.5	0.22	3.71	18 21	3.0	0.16	2.65	

Bold = Optimal pressure for the MP Rotator is 2.8 bar; 280 kPa. This can easily be achieved by using the MP Rotator with the Pro-Spray PRS40, pressure-regulated at 2.8 bar; 280 kPa.

MP ROTATOR PERFORMANCE DATA

MP815

Radius: 2.5 to 4.9 m

Adjustable Arc and Full-Circle

● Maroon and Grey: 90° to 210°

● Lt. Blue and Grey: 210° to 270°

● Olive and Grey: 360°

Arc	Pressure		Radius	Flow		Precip. mm/hr
	bar	kPa	m	m ³ /hr	l/min	■ ▲
90° 	2.1	210	4.3	0.10	1.59	21 24
	2.5	250	4.5	0.10	1.74	21 24
	2.8	280	4.6	0.11	1.85	21 24
	3.1	310	4.8	0.12	1.97	21 24
	3.5	350	4.9	0.12	2.08	21 24
	3.8	380	4.9	0.13	2.20	22 25
180° 	2.1	210	4.0	0.17	2.84	21 25
	2.5	250	4.3	0.20	3.26	21 24
	2.8	280	4.5	0.21	3.52	21 24
	3.1	310	4.6	0.22	3.63	21 24
	3.5	350	4.8	0.24	4.01	21 24
	3.8	380	4.9	0.25	4.20	21 24
210° 	2.1	210	4.0	0.20	3.33	21 25
	2.5	250	4.3	0.22	3.63	20 23
	2.8	280	4.5	0.25	4.16	21 24
	3.1	310	4.6	0.26	4.39	21 25
	3.5	350	4.8	0.28	4.69	21 24
	3.8	380	4.9	0.30	4.92	21 24
270° 	2.1	210	4.0	0.26	4.31	22 25
	2.5	250	4.3	0.28	4.69	20 23
	2.8	280	4.5	0.32	5.30	21 24
	3.1	310	4.6	0.33	5.56	21 24
	3.5	350	4.8	0.35	5.83	20 23
	3.8	380	4.9	0.37	6.09	20 23
360° 	2.1	210	4.0	0.35	5.75	22 25
	2.5	250	4.3	0.39	6.43	21 24
	2.8	280	4.5	0.42	7.08	21 24
	3.1	310	4.6	0.45	7.57	21 25
	3.5	350	4.8	0.48	8.06	21 24
	3.8	380	4.9	0.51	8.55	21 25