



Product Range




Equal tees - spigot off-take

Nominal diameter mm	Pack qty	Dimensions mm							Max weight kg	Fuse time sec	Cool time min	Product code 40 V 4.0 mm pin
		H	L	L1	L2	ØS	SL	W				
20	20*	51	100	39	39	20	58	98	0.06	40	3	WA2202
25	20	54	100	37	37	25	58	98	0.07	48	4	WA2203
32	20	62	109	42	42	32	58	109	0.09	50	6	WA2204
40	10	71	128	46	46	40	65	119	0.15	70	7	WA2205
50	10*	86	143	50	50	50	70	140	0.24	70	6	WA2206
63	5	98	158	54	54	63	70	159	0.34	50	6	WA2208
75	1	115	200	59	59	75	118	220	0.67	120	14	WA2209
90	1	131	200	63	63	90	85	206	0.83	90	9	WA2210
110	1	155	251	80	80	110	135	282	1.85	180	13	WA2211
125	1	169	247	73	73	125	95	256	1.89	120	10	WA2212
140	1	185	305	91	91	140	145	325	3.1	260	16	WA2213
160	1	217	342	101	101	160	110	350	4.39	300	21	WA2214
180	1	240	362	106	106	180	130	371	6.21	280	19	WA2215



Reducing tees - spigot off-take

Nominal diameter mm	Pack qty	Dimensions mm							Max weight kg	Fuse time sec	Cool time min	Product code 40 V 4.0 mm pin
		H	L	L1	L2	ØS	SL	W				
160x160x90	1	220	340	100	100	90	95	290	3.91	300	21	WA5350
180x180x90	1	230	361	105	105	90	110	345	4.9	280	19	WA5352



45° elbows

Nominal diameter mm	Pack qty	Dimensions mm					Max weight kg	Fuse time sec	Cool time min	Product code 40 V 4.0 mm pin
		H	L	L1	L2	W				
63	5	100	167	58	58	128	0.32	60	8	WA3316
75	5*	116	180	59	59	143	0.43	120	14	WA3317
90	5	132	222	77	77	176	0.82	80	9	WA3318
110	1	152	243	80	80	201	1.17	180	14	WA3319
125	1	175	269	82	82	228	1.84	90	7	WA3320
140	1	183	284	92	92	236	1.53	260	22	WA3321
160	1	216	326	100	100	280	3.31	300	21	WA3322
180	1	240	350	101	101	308	4.11	260	16	WA3323

Note: * Fittings available to purchase as individual items.

Always refer to the fitting and packaging label for the most up to date information.