

Qty.	Description
1	HYDRO MULTI-E 2 CRIE 15-4  Note! Product picture may differ from actual product Product No.: On request GRUNDFOS Hydro Multi-E booster sets are designed for the transfer and pressure boosting of clean water in waterworks, blocks of flats, hotels, industry, hospitals, schools, etc. GRUNDFOS Hydro Multi-E booster set consists of 2 to 4 CRIE pumps coupled in parallel and mounted on a common base frame provided with all the necessary fittings. Hydro Multi-E is mounted on a common base frame made of stainless steel (DIN W.-Nr. 1.4301). On the suction side are fitted a suction manifold (DIN W.-Nr. 1.4401 or DIN W.-Nr. 1.4571) , a pressure switch mounted on a drainable valve and an isolating valve. On the discharge side of the pumps are fitted a non-return valve, an isolating valve, a pressure gauge, two pressure transmitters mounted on a drainable valve a diaphragm tank and a stainless steel discharge manifold (DIN W.-Nr. 1.4401 or DIN W.-Nr. 1.4571). The Hydro Multi-E is fitted with an on/off-switch for the supply voltage. The Hydro Multi-E is designed for maintaining a constant pressure regardless of flow changes and fluctuation. The internal PI-controller regulates the number of running pumps and the speed of the pumps according to the required flow. The system can be operated directly on the panel of any of the pumps or via Grundfos GO (available as accessory) Besides the system features: 2 Digital outputs 2 Digital inputs (one used for dry run protection) 2 Analogue inputs (one used for discharge pressure sensor) - Multi-Master functionality 2 Limit functions - Set-point influence function - Pipe filling function - High efficient PM motors Available communication protocols: •LON •Profibus •Modbus •SMS/GSM/GPRS •GRM •BACnet •BACnet IP



Company name: Landscape Watering Systems (LWS) Ltd

Created by:


Phone: 01722 716969

Email: sales@lws.uk.com




Date: 11/12/2025

Qty.	Description
1	•Modbus TCP •PROFINET When delivered, the GRUNDFOS Hydro Multi-E booster set is factory tested and ready for operation. Liquid: Pumped liquid: Water Liquid temperature range: 5 .. 60 °C Selected liquid temperature: 20 °C Density: 998.2 kg/m³ Materials: Pump housing: Stainless steel Installation: Range of ambient temperature: 0 .. 40 °C Maximum operating pressure: 16 bar Maximum permissible inlet pressure: PN 16 bar Flange standard: DIN2642 Manifold inlet: DN 80 Manifold outlet: DN 80 Earth connection: PE Electrical data: Power (P2) main pump: 5.5 kW Mains frequency: 50 / 60 Hz Rated voltage: 3 x 380-415 V Rated current: 20 A IE Efficiency class: IE5 Start. method: electronically Enclosure class (IEC 34-5): IP54 Tank: Tank volume: 25 l Diaphragm tank: Yes Others: Net weight: 282 kg Gross weight: 340 kg Shipping volume: 1.07 m³ Language: GB



Description	Value
General information:	
Product name:	HYDRO MULTI-E 2 CRIE 15-4
Product No:	On request
EAN number:	On request
Technical:	
Max. flow:	60 m³/h
Min flow system:	6 m³/h
Max. head:	82 m
Pump name:	CRIE 15-4
Number of pumps:	2
Materials:	
Pump housing:	Stainless steel
Manifolds:	Stainless steel
Installation:	
Range of ambient temperature:	0 .. 40 °C
Maximum operating pressure:	16 bar
Maximum permissible inlet pressure:	PN 16 bar
Flange standard:	DIN2642
Manifold inlet:	DN 80
Manifold outlet:	DN 80
Earth connection:	PE
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	5 .. 60 °C
Selected liquid temperature:	20 °C
Density:	998.2 kg/m³
Electrical data:	
Power (P2) main pump:	5.5 kW
Mains frequency:	50 / 60 Hz
Rated voltage:	3 x 380-415 V
Rated current:	20 A
IE Efficiency class:	IE5
Start. method:	electronically
Enclosure class (IEC 34-5):	IP54
Tank:	
Tank volume:	25 l
Diaphragm tank:	Yes
Others:	
Net weight:	282 kg
Gross weight:	340 kg
Shipping volume:	1.07 m³
Language:	GB



Losses in fittings and valves not included
Pumped liquid = Water
Liquid temperature during operation = 20 °C
Density = 998.2 kg/m³




On request HYDRO MULTI-E 2 CRIE 15-4



Note! All units are in [mm] unless others are stated.
Disclaimer: This simplified dimensional drawing does not show all details.

On request HYDRO MULTI-E 2 CRIE 15-4



Note! All units are in [mm] unless others are stated.